Pro Force® Turbine Debris Blower

A FORCE TO BE RECKONED WITH.

The Toro® Pro Force™ debris blower delivers tremendous air power for fast removal of grass clippings, leaves, aeration cores, or other debris from your golf course, sports field, and maintained turf areas, as well as paved areas such as golf car paths, park trails or parking lots.

Operated by a wireless remote control with unmatched functionality, and with design features such as the durable one piece plastic nozzle, the Pro Force sets a new standard. Experience the new Pro Force debris



toro.com

FFATURES

blower-the better way to get your job done.

- 24.6 hp (18 kW) Kohler® Command Pro™ engine
 - Heavy-duty air cleaner.
 - Air-cooled.
 - Electronically-governed.
- Efficient turbine-type axial flow fan assembly design.
- Wireless Remote Control
 - Start and stop the engine from the utility vehicle platform for complete operational control.
 - 360-degree nozzle rotation in either direction.
 - Adjust engine throttle for power through full RPM range of operation.
 - Ergonomic weather-resistant design.

- Single piece, impact resistant plastic nozzle.
- Fully-enclosed exhaust system.
- Rugged construction includes steel trailer frame and sturdy plastic wheel fenders.
- Heavy-Duty Trailer & Tow Hitch is adjustable in height and length to accommodate different towing utility vehicles.
- Warranty: two-year or 1,500-hour limited manufacturer's warranty.



PRO FORCE DEBRIS BLOWER

Pro Force™

The Pro Force™ is a self-contained engine-driven Debris Blower operated with a handheld wireless RF controller. It utilizes a high-efficiency turbine-type fan assembly designed to deliver greater air power to clear turf or pavement of leaves, grass clippings, twigs, pine needles or other undesirable debris.



MODEL 44538*

| ENGINE | 24.6 hp (18.3 kW) Kohler® Command Pro™ 725 cc, gas, 2-cylinder, air-cooled, electronically-governed. |
|-----------------------|---|
| FAN DESIGN | High-efficiency, axial flow, turbine-type fan assembly |
| CONTROL | Handheld wireless RF controller provides capability to start and stop the engine, adjust engine throttle up and down for high to low RPM range of operation, and rotate nozzle 360 degrees in either direction. Ergonomic, weather-resistant. |
| NOZZLE | Single piece, impact resistant plastic with 13" (33 cm) outlet diameter. |
| ROTOR DIAMETER | 14" (35.5 cm). |
| FAN ASSEMBLY DIAMETER | 14" (35.5 cm). |
| WEIGHT | 475 lbs (215.4 kg). |
| LENGTH | Standard 97" (246 cm) from adjustable tow hitch to nozzle outlet. 18" (45.7 cm) adjustable length for length range of 79"-115" (200.6 cm - 292.1 cm). |
| WIDTH | 48" (122 cm). |
| HEIGHT | 44" (111.7 cm). |
| TOW-BEHIND TRAILER | Lawn-tractor-style hitch (category 1). Three hole locations to accomodate varying reciever heights. |
| TIRE SIZE | 20 x 10-8, 4-ply turf tire. |
| FENDERS | Custom injection-molded plastic. |
| WARRANTY | Two-year or 1,500-hour limited warranty.* |
| | |

Rev. 1/16

The Pro Force is manufactured in Tomah, WI ISO 9002 Certified Plant.



toro.com

Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801 Fax: (1) 952 887 8258

Printed in U.S.A. ©2016 The Toro Company. All Rights Reserved. 200-7320 GB







facebook.com/ToroCompany twitter.com/TheToroCompany youtube.com/ToroCompanyEurope



Count on it,

^{*}Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.